

OLAKOR

INTERIOR DECORATIVE LACQUERED GLASS


AURYS
UPLIFT INTERIORS BY GLASS



**UPLIFT INTERIORS
BY GLASS**

2025



CONTENT

OLAKOR.....p.3
Lacquered glass

TRENDS.....p.5

COLLECTIONS.....p.6
Pastels | Classics | Tonics | Mattes

COLOR PALETTE.....p.10

COLOR'UP.....p.11
Colour library

OFORCE LACQUERED.....p.12
Lacquered safety glass

TECHNICAL SPECIFICATIONS.....p.13



OLAKOR

DECORATIVE LACQUERED GLASS

OLAKOR is a range of lacquered glass. Their opaque and coloured appearance is achieved by applying a highly resistant layer of lacquer to one side of the glass.

RANGE

OLAKOR lacquered glass is available in 26 shades. The frosted lacquers are available in 5 main shades. The COLOR'UP shade library is available in a wide range of colors to suit every style.

APPLICATIONS

Furnitures: wardrobes, tables, cabinets, etc.
Doors and partitions
Wall covering: corridors, lobbies, etc.

BENEFITS

OLAKOR combines the aesthetics of lacquer with glass shine :

- Wide choice of shades, from classic to contemporary styles
- Harmonious integration with natural interior materials
- Adaptable to different spaces and moods

SUSTAINABILITY

Made from durable materials such as glass, OLAKOR is a tough interior panelling solution built to last.

OLAKOR

Aesthetic - Functional - Sustainable



LACQUERED GLASS SOLUTIONS

Harmonious colors to enhance the interior. OLAKOR is a range of lacquered glass combining aesthetics and performance, designed to bring a touch of refinement elegance to interior design.

OUR LACQUERED GLASS RANGE

OLAKOR is a range of lacquered glass. Their opaque, colored appearance is obtained by depositing a layer of highly resistant lacquer on one side of the glass. A satin finish is available for certain colors.

- An infinite choice of colors and finishes: a rich and varied palette of colors to suit every style and taste. With colors ranging from refined neutrals to vivid shades, OLAKOR makes interiors sublime.
- Industrial manufacturing: lacquered glass is made from high-quality glass using a standardized production method for optimum results.
- Technical expertise: depending on your needs, our teams will guide you through your project from A to Z.

OUR COMMITMENTS: QUALITY AND SUSTAINABILITY

Made from high-quality float glass, our lacquered glass offers a high level of finish and scratch resistance. It is also possible to apply a SAFE film to the back to withhold broken glass in the event of an impact.

For greater security, our ultra-resistant OFORCE lacquered glass, made from laminated glass, is also available. Lacquered OFORCE is more resistant than conventional lacquered glass, offering enhanced impact resistance. In the event of breakage, the lacquered laminated glass remains in place and the fragments adhere to the PVB interlayer, thereby reducing the risk of injury. Personal protection is guaranteed thanks to its resistance properties.

Manufactured using an industrial process, OLAKOR and OFORCE LACQUERED lacquered glasses features a uniform application of lacquer. These glasses have a low level of VOC emissions.

INFINITE APPLICATIONS TO ENHANCE INTERIOR

Endless applications to enhance interior spaces:

- Refined walls: lacquered glass wall cladding for an original look and to give character to the living room, bedroom or hallway with coloured gloss or matt lacquered glass panels.
- Coloured gloss or satin furniture: lacquered glass surfaces for furniture and doors with an ultra-contemporary design effect.
- Unique splashbacks: easy to clean and hygienic, lacquered glass splashbacks bring a touch of modernity and elegance to the kitchen area.



TRENDS



PASTEL WHITE

BALTIC



TAUPE BROWN

INTERIOR DESIGN



SAGE

CLAY




OLAKOR | *Collection - Pastels*

COLLECTION

PASTELS

Pastel shades are characterised by soft, delicate colours. These shades create a soothing, warm atmosphere in living spaces. Pastels colors cover furniture or walls with a subtle touch, enhancing the design effect.

	ALPINE WHITE DL210
	PASTEL WHITE DL191
	OFF WHITE DL224
	WATER GREEN DL207



OLAKOR | *Collection - Timeless*

COLLECTION

TIMELESS

Timeless colours are a reliable choice for sustainable interiors with classic shades. These neutral shades create an elegant, sophisticated atmosphere in living spaces. The versatility of these shades means you can play with other materials and textures to reveal coloured lacquered glass.

TAUPE BROWN DL280	COFFEE DL183	CHOCOLATE BROWN DL180	
	TERRA DL181		
	PLUM DL155		
DEEP BLACK DL227	DARK GREY DL228	METALLIC SILVER DL219	PEARL GREY DL177
CEDAR DL317	CLAY DL314	SAGE DL315	



OLAKOR | *Collection - Tonics*

COLLECTION

TONICS

Bright, bold colors bring character and intensity to interiors. To create a personalised atmosphere with a touch of dynamism and energy, colored lacquered glass has a special place in interiors.





COLLECTIONS

MATÉS

Matt frosted glass has a smooth, velvety surface. Combined with lacquer, the glass has a silky, tinted finish. This process gives the glass a delicate, refined look, ideal for creating a cosy, elegant atmosphere in the home. OLAKOR MATÉ is available in a range of timeless colours.

BEIGE GALET
DL242

TAUPE GREY
DL243

ALPINE WHITE
DL210

ANTHRACITE
DL322


DEEP BLACK
DL227

OLAKOR - COLOR PALETTE


PASTELS




ALPINE WHITE
DL210




PASTEL WHITE
DL191



SATIN WHITE
DL120



OFF WHITE
DL224



WATER GREEN
DL207

OLAKOR MATÉ



ALPINE WHITE
DL210




BEIGE GALET
DL242



TAUPE GREY
DL243



ANTHRACITE
DL322



DEEP BLACK
DL227

TIMELESS



COFFEE
DL183



TAUPE BROWN
DL280



TERRA
DL181



CHOCOLATE
BROWN DL180



PLUM
DL155



DEEP BLACK
DL227



DARK GREY
DL228



METALLIC SILVER
DL219



PEARL GREY
DL177



CEDAR
DL317



CLAY
DL314




SAGE
DL315


TONICS



LIME GREEN
DL296



SKY BLUE
DL294



AQUA MARINE
DL297



BALTIC
DL316



MIDNIGHT BLUE
DL152



PETAL PINK
DL293



RASPBERRY
DL139



PURPLE RED
DL130



RED PASSION
DL252

OLAKOR - COLOR'UP

COLOUR LIBRARY


COLOR'UP

A world of colour, with a wide range from subtle shades to vibrant tones. Our COLOR'UP palette allows you to design interior with creativity and a unique style.



With OLAKOR COLOR'UP, bring color to interiors:

- **A wide range of colours:** from neutral tones to the brightest colours, pastel or metallic shades, our library of shades offers many possibilities for coloured lacquered glass.
- **Colour for all kinds of applications:**
 - > Furnitures: wardrobes, tables, cabinets, etc
 - > Doors and partitions
 - > Wall covering : corridors, lobbies, etc
- **Custom colours can be developed:** a solution for projects requiring a unique shade or a particular visual effect. Printed glass can also be lacquered, depending on the desired result.
 - > *MOQ for specific colour development: 1000 m²*



OLAKOR
Master-Soft.

TEXTURED LACQUERED GLASS



SAFETY LACQUERED GLASS

OFORCE LACQUERED is a range of lacquered safety glass. Based on laminated glass, lacquer adds colour and gloss to the glass.

Lacquered OFORCE is stronger than conventional lacquered glass, offering improved performance against impact. In the event of breakage, OFORCE LACQUERED hold and the fragments adhere to the PVB interlayer, reducing the risk of injury. Personal protection is guaranteed thanks to its resistance properties.


BENEFITS

Impact resistance

Lacquered glass is laminated, which makes it much more resistant to shocks and impacts than ordinary lacquered glass. It is therefore less likely to shatter in the event of a fall or breakage.

Protection against injuries

In the event of breakage, toughened lacquered glass shatters into small, non-sharp pieces, while the laminated lacquered glass hold in place thanks the PVB



SPECIFICATIONS

TECHNICAL INFORMATION

OFORCE LACQUERED glass features a laminated glass substrate coated with an organic lacquer, delivering a high-gloss, colorful appearance

FEATURES

Thickness (mm)	22.1	33.1
Dimensions (mm)	3210 x 2250 mm	3210 x 2250 mm
Weight (kg/m ²)	10.5/m ²	16/m ²

Available on demand : 33.2 and 44.2

Lacquer available colors :

- Deep Black - DL227
- Alpine White - DL210

ENVIRONMENT

OFORCE LACQUERED glass contributes to a healthy and non-polluted environment. According to the latest French regulations on Volatile Organic Compounds (VOCs) and construction products (decree of April 19, 2011), OFORCE LACQUERED is classified A+, the highest level.



PROCESSING

OFORCE LACQUERED transformation should be carried out in similar conditions to those for laminated glass. In general, it is recommended that the coating on the back of the mirror should not be damaged (scratched or cracked). Aggressive chemicals that could damage the lacquer should also be avoided.

The following transformations can be carried out on lacquered laminated glass:

- **Cutting** : must be performed with specific adjustments compared to a standard laminated glass without silver and protective back paint. For complete details of the different cutting steps, please consult our OFORCE Processing Guide
- **Shaping** : the product can be edged in the same way as laminated glass. For more information on edging, please contact our technical teams
- **Other transformations** : consult us

MAINTENANCE

Easy to maintain, OFORCE LACQUERED can be cleaned with a clean, soft cloth and the usual nonabrasive

INSTALLATION

OFORCE LACQUERED glass is exclusively for interior use, in accordance with current regulations and best practices. It can be installed quickly and easily using mechanical fixings (rebated or with fixing brackets) or adhesive, such as neutral silicone or double-sided tape.

Regardless of the chosen fixing method, it is essential to:

- Install the lacquered glass in front of a flat, clean, dry wall, free from aggressive substances
- *Position the lacquered side facing the wall; allow a gap of 1 to 2 mm between volumes*
- *Ensure proper sealing; do not expose the product to temperatures exceeding 50°C, as this may cause breakage or slight color changes over time*

For bonding, use a neutral silicone like DOW CORNING 817. A preliminary test is advisable. For more details, consult our R&D team.

STORAGE

Glass should be stored in a clean, dry place. OFORCE LACQUERED should not be exposed to high humidity or wide variations in temperature, which could lead to condensation. Exposure to corrosive components such as chlorides and sulphides should also be avoided. Do not scratch the protective coating on the back or edges of the glass.

LOGISTICS

Standard packaging for OFORCE LACQUERED (3210 mm x 2250 mm) is in framed bulk. A full lorry consists of 10 framed bulk units.

Dimensions	Thickness	Packing	Weight
3210 x 2250 mm	4 mm	30 x framed bulk	2,2 t
		40 x single pile	2,8 t
	6 mm	20 x framed bulk	2,2 t
		26 x single pile	2,8 t



SPECIFICATIONS

TECHNICAL INFORMATION

OLAKOR lacquered glass features a glass substrate coated with an organic lacquer, offering a vibrant, glossy appearance. A matte finish option is also available with OLAKOR MATÉ.

FEATURES

Thickness	4 mm	6 mm
Dimensions	3210 x 2250 mm or 3210 x 2550 mm	3210 x 2250 mm or 3210 x 2550 mm
Weight (kg/m ²)	10kg/m ²	15kg/m ²

ENVIRONNEMENT

OLAKOR glass contributes to a healthy and non-polluted environment. According to the latest French regulations on Volatile Organic Compounds (VOCs) and construction products (decree of April 19, 2011), OLAKOR is classified A+, the highest level.



PROCESSING

OLAKOR transformation should be carried out in similar conditions to those for mirrors. In general, it is recommended that the coating on the back of the mirror should not be damaged (scratched or cracked). Aggressive chemicals that could damage the lacquer should also be avoided.

The following transformations can be carried out on lacquered glass:

- **Cutting** : place volumes on a clean table to protect the lacquer layer from scratches or any other damage
- **Shaping** : standard edging machines can be used (single or double edge, chamfering, CNC). It is advisable to have a slight inclination to the edges of the glass when grinding
- **Safety** : a protective SAFE film can be applied to the back of the mirror to prevent injuries in possible occurrence of breakage
- **Other transformations** : drilling, engraving, chamfering, sandblasting and screen printing are possible. Tests must be carried out before to check the compatibility of the process and ensure mirror integrity. Lacquered glasses cannot be: laminated, tempered or double-glazed.

MAINTENANCE

Easy to maintain, OLAKOR can be cleaned with a clean, soft cloth and the usual nonabrasive mirror cleaner. Never use strong acids, bases or oxidisers.

INSTALLATION

OLAKOR glass is exclusively for interior use, in accordance with current regulations and best practices. It can be installed quickly and easily using mechanical fixings (rebated or with fixing brackets) or adhesive, such as neutral silicone or double-sided tape. OLAKOR SAFE glass can also be mechanically fixed. Regardless of the chosen fixing method, it is essential to:

- Install the lacquered glass in front of a flat, clean, dry wall, free from aggressive substances
- *Position the lacquered side facing the wall; allow a gap of 1 to 2 mm between volumes*
- *Ensure proper sealing; do not expose the product to temperatures exceeding 50°C, as this may cause breakage or slight color changes over time*

For installations near a gas hob, we recommend using OLAKOR on a tempered glass base. For example, the OLAKOR Silver Metallic reference should only be used in dry areas.

For bonding, we recommend using a neutral silicone such as DOW CORNING 817 or an equivalent product. A preliminary test is recommended to ensure compatibility with the surfaces and the lacquered glass. For any questions regarding a specific reference, please contact our R&D team.

STORAGE

Glass should be stored in a clean, dry place. OLAKOR should not be exposed to high humidity or wide variations in temperature, which could lead to condensation. Exposure to corrosive components such as chlorides and sulphides should also be avoided. Do not scratch the protective coating on the back or edges of the glass.

LOGISTICS

Standard packaging for OFORCE LACQUERED (3210 mm x 2250 mm) is in framed bulk.

A full lorry consists of 10 framed bulk units.

FRAMED BULK (BOX)			
Dimensions	Thickness	Packing	Weight
3210 x 2250 mm	4 mm	30 x framed bulk	2,2 t
3210 x 2250 mm	6 mm	20 x framed bulk	
PILE SEULE (INLOADER)			
3210 x 2250 mm	4 mm	40 x single pile	2,8 t
3210 x 2550 mm		35 x single pile	
3210 x 2250 mm	6 mm	26 x single pile	
3210 x 2550 mm		23 x single pile	



AURYS INDUSTRIES

ZI de Pommenauque – 50500 Carentan-Les-Marais – FRANCE

+33 (0)2 33 71 65 00

info@aurys-industries.com